

HIGH PERFORMANCE BRAIDED REDUCING CONNECTORS

REDUCER—FLANGE X FLANGE

- **Stainless Steel**
Annular Hose with Stainless Steel Braid
- **150# Drilling Carbon Steel**
Plate Flange

Large Hose ID	Small Hose ID	OAL	Approx. Wt. (lbs.)	Max Working Pressure @ 70°F
2"	1-1/2"	13"	12	435
2-1/2"	1-1/2"	13"	15	350
2-1/2"	2"	13"	15	350
3"	2"	13"	18	325
3"	2-1/2"	13"	19	325
4"	2"	13"	22	270
4"	2-1/2"	13"	25	270
4"	3"	13"	25	270
5"	2-1/2"	16"	30	200
5"	3"	16"	30	200
5"	4"	16"	34	200
6"	3"	17"	38	185
6"	4"	17"	40	185
6"	5"	17"	42	185
8"	4"	18"	55	235
8"	5"	18"	58	235
8"	6"	18"	60	235
10"	6"	20"	85	260
10"	8"	20"	95	260
12"	10"	22"	125	160

REDUCER—FLANGE X GROOVE END

- **Stainless Steel**
Annular Hose with Stainless Steel Braid
- **150# Drilling Carbon Steel Plate**
Flange X Sch 40 Precision Grooved End

Large Hose ID	Small Hose ID	OAL	Approx. Wt. (lbs.)	Max Working Pressure @ 70°F
2"	1-1/2"	14"	12	435
2-1/2"	1-1/2"	14"	15	350
2-1/2"	2"	14"	15	350
3"	2"	14"	18	325
3"	2-1/2"	14"	19	325
4"	2"	16"	22	270
4"	2-1/2"	16"	25	270
4"	3"	16"	25	270
5"	2-1/2"	18"	30	200
5"	3"	18"	30	200
5"	4"	18"	34	200
6"	3"	19"	38	185
6"	4"	19"	40	185
6"	5"	19"	42	185
8"	4"	20"	55	235
8"	5"	20"	58	235
8"	6"	20"	60	235
10"	6"	22"	85	260
10"	8"	23"	95	260
12"	10"	23"	125	160

QUICK DELIVERY

CUSTOM SIZES AVAILABLE

Toll Free: 877-462-1007
 Fax: 847-462-1450
 24/7 Emergency Service: 847-337-9459

www.duraflexinc.com



© Copyrights 2004-2009 Duraflex, Inc.™ All rights reserved.

765 Industrial Drive
 Cary, IL 60013
 Em: duraflex@duraflexinc.com

HIGH PERFORMANCE BRAIDED FLEXIBLE CONNECTORS

5
YEAR
WARRANTY

STOCK
PUMP
CONNECTORS

MALE PIPE THREADS



- Stainless Steel Annular Hose with Stainless Steel Braid
- Carbon Steel Male Pipe Threads

I.D.	OAL	Approx. Wt. (lbs.)	Max Working Pressure @ 70°F
1/2"	6-1/2"	1/2	825
3/4"	7"	3/4	600
1"	8"	1	580
1-1/4"	8-1/2"	1-1/4	535
1-1/2"	9"	1-1/2	510
2"	10-1/2"	2-1/2	442

FLANGE



- Stainless Steel Annular Hose with Stainless Steel Braid
- 150# Drilling Carbon Steel Black Enamel Baked Plate Flange

I.D.	OAL	Approx. Wt. (lbs.)	Max Working Pressure @ 70°F
2"	9"	11	442
2-1/2"	9"	14	390
3"	9"	15	325
4"	9"	20	270
5"	11"	28	185
6"	11"	33	170
8"	12"	52	185
10"	13"	75	180

